

MODEL 5x16

5-inch Filterless Fuel Purifier



APPLICATION / BEST FIT

Stationary diesel pumps, generators and equipment; stated engine range 400-1,200 HP.

PERFORMANCE

Removes 99% of water and 95-98% of heavy particles.

OPERATING PRINCIPLE

Long residence time and proprietary media separate free water and heavy contamination before fuel reaches the engine filtration system. No replaceable filter element.

TECHNICAL SPECIFICATIONS

PARAMETER	OFFICIAL SPECIFICATION
Product	Fuel Purifier
Model	5x16
Maximum Flow	15 GPM maximum
Inlet / Outlet	1/2 in. NPT forged steel
Top / Drain Ports	1/2 in. NPT
Sensor Port	1/8 in. NPT
Size	5 in. dia. x 17.8 in. tall
Gross Weight	15 lb (6.8 kg)
Finish	White epoxy powder coat

COMMON FEATURES

Filterless operation | Vertical installation | Bottom drain | Five-year warranty

OPTIONS / NOTES

MG-03 mounting strap, MG-49 sensor strap, MG-44 tripod legs, Model 06-5 water sensor

Source: Dieselcraft Product Portfolio - Fuel Purification section. Specifications are subject to change without notice. Confirm application requirements before ordering.

Dieselcraft Fluid Engineering | A Magnum Group Company | Auburn, California USA | sales@dieselcraft.com | dieselcraft.com