

MODEL 5x24

5-inch Filterless Fuel Purifier



APPLICATION / BEST FIT

Circulation pumps rated 4-7 GPM; stated engine range 600-1,500 HP.

PERFORMANCE

Removes 99% of water and 95-98% of heavy particles.

OPERATING PRINCIPLE

Long residence time and proprietary media separate free water and heavy contamination before fuel reaches the engine filtration system. No replaceable filter element.

TECHNICAL SPECIFICATIONS

PARAMETER	OFFICIAL SPECIFICATION
Product	Fuel Purifier
Model	5x24
Maximum Flow	20 GPM maximum
Inlet / Outlet	1 in. NPT forged steel
Top / Drain Ports	1/2 in. NPT
Sensor Port	1/8 in. NPT
Size	5 in. dia. x 25.48 in. tall
Gross Weight	18 lb (8.2 kg)
Finish	Gray epoxy powder coat

COMMON FEATURES

Filterless operation | Vertical installation | Bottom drain | Five-year warranty

OPTIONS / NOTES

MG-03 mounting strap, MG-49 sensor strap, MG-44 tripod legs, Model 06-5 water sensor

Source: Dieselcraft Product Portfolio - Fuel Purification section. Specifications are subject to change without notice. Confirm application requirements before ordering.

Dieselcraft Fluid Engineering | A Magnum Group Company | Auburn, California USA | sales@dieselcraft.com | dieselcraft.com