

MODEL 8x30

8-inch Filterless Fuel Purifier



APPLICATION / BEST FIT

For stationary diesel pumps, gen sets, locomotives, fuel docks and equipment. Stated engine range 1,200-2,000 HP.

PERFORMANCE

Removes 99% of water and 95-98% of heavy particles. NOT FOR USE WITH GASOLINE.

OPERATING PRINCIPLE

Long residence time and proprietary media separate free water and heavy contamination before fuel reaches the engine filtration system. No replaceable filter element.

TECHNICAL SPECIFICATIONS

PARAMETER	OFFICIAL SPECIFICATION
Product	Universal Fuel Purifier
Model	8x30
Maximum Flow	25 GPM / 95 LPM
Inlet / Outlet	2 in. NPT forged steel
Top Port	1 in. NPT
Sensor Port	1/8 in. NPT
Diameter	8 in. / 203 mm
Overall Height	31.93 in.
Gross Weight	40 lb / 18 kg
Finish	Gray epoxy powder coat

COMMON FEATURES

Filterless operation | Vertical installation | Bottom drain | Five-year warranty

STANDARD EQUIPMENT

Includes mounting strap, 06-5 water sensor and drain valve. Power supply is optional.

OPTIONS / NOTES

Custom colors available. Power supply optional. Optional 06-6SP water sensor offers additional output for alarm systems.

Source: Dieselcraft Product Portfolio - Fuel Purification section. Specifications are subject to change without notice. Confirm application requirements before ordering.

Dieselcraft Fluid Engineering | A Magnum Group Company | Auburn, California USA | sales@dieselcraft.com | dieselcraft.com