

MODEL 8x51

8-inch Filterless Fuel Purifier



APPLICATION / BEST FIT

For stationary diesel pumps, fuel docks and equipment. Stated engine range 1,200-2,000 HP.

PERFORMANCE

Removes 99% of water and 95-98% of heavy particles. NOT FOR USE WITH GASOLINE.

OPERATING PRINCIPLE

Long residence time and proprietary media separate free water and heavy contamination before fuel reaches the engine filtration system. No replaceable filter element.

TECHNICAL SPECIFICATIONS

PARAMETER	OFFICIAL SPECIFICATION
Product	Universal Fuel Purifier
Model	8x51
Maximum Flow	40 GPM / 151 LPM
Inlet / Outlet	2 in. NPT forged steel
Top Port	1 in. NPT
Sensor Port	1/8 in. NPT
Diameter	8 in. / 203 mm
Vessel Height	31.93 in. (tank only)
Port Height with Legs	42.6 in. to 46.6 in. adjustable
Gross Weight	68 lb / 31 kg
Finish	Gray epoxy powder coat

COMMON FEATURES

Filterless operation | Vertical installation | Bottom drain | Five-year warranty

STANDARD EQUIPMENT

Adjustable legs included. Tripod / mounting hardware supplied with the unit. 8x51 supplied as pictured.

OPTIONS / NOTES

Optional water sensor, sensor mount and power supply available at additional cost.

Source: Dieselcraft Product Portfolio - Fuel Purification section. Specifications are subject to change without notice. Confirm application requirements before ordering.

Dieselcraft Fluid Engineering | A Magnum Group Company | Auburn, California USA | sales@dieselcraft.com | dieselcraft.com